

GENERAL DESCRIPTION


The 74AHC1G08 is a single 2-input positive-AND gate with high-speed CMOS inputs. The supply voltage can range from 2.0V to 5.5V. The device implements the Boolean function $Y = A \cdot B$ or $Y = \overline{A + B}$.

The 74AHC1G08 is available in Green SC70-5 and SOT-23-5 packages. It operates over an ambient temperature range of -40°C to $+125^{\circ}\text{C}$.

FEATURES

- **Wide Supply Voltage Range: 2.0V to 5.5V**
- **+8mA/-8mA Output Current at $V_{CC} = 5.0\text{V}$**
- **Low Quiescent Current: $I_{CC} = 2\mu\text{A (MAX)}$**
- **Propagation Delay:**
 $t_{PD} = 4.5\text{ns (TYP)}$ at $V_{CC} = 5\text{V}$ and $C_L = 50\text{pF}$
- **All Inputs with Schmitt-Trigger Action**
- **-40°C to $+125^{\circ}\text{C}$ Operating Temperature Range**
- **Available in Green SC70-5 and SOT-23-5 Packages**


LOGIC SYMBOL



APPLICATIONS

Computing: Server, PC and Notebook
 Medical Equipment
 Industrial Equipment
 Telecom Equipment
 Wireless Equipment
 Battery Powered Equipment

LOGIC DIAGRAM



FUNCTION TABLE

INPUTS		OUTPUT
A	B	Y
H	H	H
L	X	L
X	L	L

$$Y = A \cdot B \text{ or } Y = \overline{A + B}$$

H = High Voltage Level

L = Low Voltage Level


X = Don't Care

PACKAGE/ORDERING INFORMATION

Table with 6 columns: MODEL, PACKAGE DESCRIPTION, SPECIFIED TEMPERATURE RANGE, ORDERING NUMBER, PACKAGE MARKING, PACKING OPTION. It lists two variants for the 74AHC1G08 model: SC70-5 and SOT-23-5, both with a temperature range of -40°C to +125°C.

MARKING INFORMATION

NOTE: XX = Date Code.



Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

ABSOLUTE MAXIMUM RATINGS (1)

Table of absolute maximum ratings including: Supply Voltage (VCC), Input Voltage (VI), Output Voltage (VO), Input Clamping Current (IIK), Output Clamping Current (IOK), Continuous Output Current (IO), Continuous Current (ICC or GND), Junction Temperature, Storage Temperature Range, Lead Temperature, ESD Susceptibility (HBM, CDM).

RECOMMENDED OPERATING CONDITIONS

Table of recommended operating conditions including: Supply Voltage Range, Input Voltage Range, Output Voltage Range, Input Transition Rise or Fall Rate (dt/dV) for VCC = 3.3V and 5.0V, and Operating Temperature Range.

OVERSTRESS CAUTION


- 1. Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability. Functional operation of the device at any conditions beyond those indicated in the Recommended Operating Conditions section is not implied.
2. The input and output voltage ratings may be exceeded if the input and output clamp current ratings are observed.
3. The performance capability of a high-performance integrated circuit in conjunction with its thermal environment can create junction temperatures which are detrimental to reliability.

ESD SENSITIVITY CAUTION

This integrated circuit can be damaged if ESD protections are not considered carefully. SGMICRO recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage. ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because even small parametric changes could cause the device not to meet the published specifications.

DISCLAIMER

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.

PIN CONFIGURATIONS**PIN DESCRIPTION**

PIN	NAME	FUNCTION
1	A	Data Input.
2	B	Data Input.
3	GND	Ground.
4	Y	Data Output.
5	V _{cc}	Supply Voltage.

ELECTRICAL CHARACTERISTICS(Full = -40°C to +125°C, all typical values are measured at $T_A = +25^\circ\text{C}$, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	TEMP	MIN	TYP	MAX	UNITS	
High-Level Input Voltage	V_{IH}	$V_{CC} = 2.0\text{V}$	Full	1.5			V	
		$V_{CC} = 3.0\text{V}$	Full	2.1				
		$V_{CC} = 5.5\text{V}$	Full	3.85				
Low-Level Input Voltage	V_{IL}	$V_{CC} = 2.0\text{V}$	Full			0.5	V	
		$V_{CC} = 3.0\text{V}$	Full			0.9		
		$V_{CC} = 5.5\text{V}$	Full			1.65		
High-Level Output Voltage	V_{OH}	$V_I = V_{IH}$ or V_{IL}	$V_{CC} = 2.0\text{V}, I_{OH} = -50\mu\text{A}$	Full	1.9	1.99	V	
			$V_{CC} = 3.0\text{V}, I_{OH} = -50\mu\text{A}$	Full	2.9	2.99		
			$V_{CC} = 4.5\text{V}, I_{OH} = -50\mu\text{A}$	Full	4.4	4.49		
			$V_{CC} = 3.0\text{V}, I_{OH} = -4\text{mA}$	Full	2.48	2.8		
			$V_{CC} = 4.5\text{V}, I_{OH} = -8\text{mA}$	Full	3.8	4.2		
Low-Level Output Voltage	V_{OL}	$V_I = V_{IH}$ or V_{IL}	$V_{CC} = 2.0\text{V}, I_{OL} = 50\mu\text{A}$	Full		0.01	0.1	V
			$V_{CC} = 3.0\text{V}, I_{OL} = 50\mu\text{A}$	Full		0.01	0.1	
			$V_{CC} = 4.5\text{V}, I_{OL} = 50\mu\text{A}$	Full		0.01	0.1	
			$V_{CC} = 3.0\text{V}, I_{OL} = 4\text{mA}$	Full		0.2	0.44	
			$V_{CC} = 4.5\text{V}, I_{OL} = 8\text{mA}$	Full		0.3	0.44	
Input Leakage Current	I_I	$V_{CC} = 0\text{V to } 5.5\text{V}, V_I = 5.5\text{V or GND}$	+25°C		±0.1	±1	μA	
Supply Current	I_{CC}	$V_{CC} = 1.65\text{V to } 5.5\text{V}, V_I = 5.5\text{V or GND}, I_O = 0\text{A}$	+25°C		1	2	μA	
Input Capacitance	C_I	$V_{CC} = 5\text{V}, V_I = V_{CC}$ or GND	+25°C		5		pF	

DYNAMIC CHARACTERISTICS

(See Figure 1 for test circuit, see Figure 2 for waveforms. Full = -40°C to +125°C, all typical values are measured at $T_A = +25^\circ\text{C}$ and $V_{CC} = 3.3\text{V}$ and $V_{CC} = 5.0\text{V}$ respectively, unless otherwise noted.)


PARAMETER	SYMBOL	CONDITIONS	TEMP	MIN ⁽¹⁾	TYP	MAX ⁽¹⁾	UNITS	
Propagation Delay ⁽²⁾	t_{PD}	A or B to Y, $V_{CC} = 3.0\text{V}$ to 3.6V , See Table 1	$C_L = 15\text{pF}$	+25°C		4.0	5.5	ns
				Full	0.5		7.5	
			$C_L = 50\text{pF}$	+25°C		5.5	7.5	
				Full	1.0		12.5	
		A or B to Y, $V_{CC} = 4.5\text{V}$ to 5.5V , See Table 1	$C_L = 15\text{pF}$	+25°C		3.5	5.0	ns
				Full	0.5		6.0	
			$C_L = 50\text{pF}$	+25°C		4.5	6.0	
				Full	1.0		8.5	
Power Dissipation Capacitance ⁽³⁾	C_{PD}	No load, $f_i = 1\text{MHz}$, $V_{CC} = 5\text{V}$	+25°C		9.5		pF	

NOTES:

- Specified by design and characterization; not production tested.
- t_{PD} is the same as t_{PLH} and t_{PHL} .
- C_{PD} is used to determine the dynamic power dissipation (P_D in μW).

$$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o)$$
 where:
 f_i = Input frequency in MHz.
 f_o = Output frequency in MHz.
 C_L = Output load capacitance in pF.
 V_{CC} = Supply voltage in Volts.
 N = Number of inputs switching.
 $\Sigma(C_L \times V_{CC}^2 \times f_o)$ = Sum of outputs.

TEST CIRCUIT



Test conditions are given in Table 1.

Definitions for test circuit:

C_L : Load capacitance (includes jig and probe).


R_T : Termination resistance (equals to output impedance Z_O of the pulse generator).

Figure 1. Test Circuit for Measuring Switching Times

Table 1. Test Conditions

SUPPLY VOLTAGE	INPUT		LOAD	TEST
V_{CC}	V_I	t_R, t_F	C_L	
2.0V to 5.5V	V_{CC}	$\leq 3.0ns$	15pF, 50pF	t_{PHL}, t_{PLH}

WAVEFORMS



Test conditions are given in Table 1.

Measurement points are given in Table 2.

Logic levels: V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Figure 2. Input (A or B) to Output (Y) Propagation Delays

Table 2. Measurement Points

SUPPLY VOLTAGE	INPUT		OUTPUT
V_{CC}	V_I	$V_M^{(1)}$	V_M
2.0V to 5.5V	V_{CC}	$0.5 \times V_{CC}$	$0.5 \times V_{CC}$

NOTE:

1. The measurement points should be V_{IH} or V_{IL} when the input rising or falling time exceeds 3.0ns.


REVISION HISTORY

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.



Changes from Original (JANUARY 2024) to REV.A	Page
Changed from product preview to production data.....	All

PACKAGE OUTLINE DIMENSIONS

SC70-5



RECOMMENDED LAND PATTERN (Unit: mm)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	0.800	1.100	0.031	0.043
A1	0.000	0.100	0.000	0.004
A2	0.800	1.000	0.031	0.039
b	0.150	0.350	0.006	0.014
c	0.080	0.220	0.003	0.009
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.65 TYP		0.026 TYP	
e1	1.300 BSC		0.051 BSC	
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°



NOTES:

1. Body dimensions do not include mode flash or protrusion.
2. This drawing is subject to change without notice.



PACKAGE INFORMATION

PACKAGE OUTLINE DIMENSIONS

SOT-23-5



RECOMMENDED LAND PATTERN (Unit: mm)



Symbol	Dimensions In Millimeters		
	MIN	MOD	MAX
A	-	-	1.450
A1	0.000	-	0.150
A2	0.900	-	1.300
b	0.300	-	0.500
c	0.080	-	0.220
D	2.750	-	3.050
E	1.450	-	1.750
E1	2.600	-	3.000
e	0.950 BSC		
e1	1.900 BSC		
L	0.300	-	0.600
θ	0°	-	8°
ccc	0.100		

NOTES:

1. This drawing is subject to change without notice.
2. The dimensions do not include mold flashes, protrusions or gate burrs.
3. Reference JEDEC MO-178.

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
SC70-5	7"	9.5	2.40	2.50	1.20	4.0	4.0	2.0	8.0	Q3
SOT-23-5	7"	9.5	3.20	3.20	1.40	4.0	4.0	2.0	8.0	Q3

DD0001

CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
7" (Option)	368	227	224	8
7"	442	410	224	18

DD0002